MA-707 Portable Wireless PA System

Introduction

For over 16 years, MA-707 has been mass-produced and sold in over 75 countries and it remains a market-leading system as MIPRO ensures product design, craftsmanship and reliability are second to none.

MA-707 is a versatile and rugged system that can be used indoors and outdoors and provides excellent full range music reproduction as well as quality intelligible speech. It offers an ideal public address solution for medium to large crowds.

Ideal applications include: Schools, Places of worship, Presentations, seminars and meetings, Shopping center & trade show presentations and promotions, Aerobic & fitness centers, Parades & fetes, Street performers, Recreational & social activities, Hobby & leisure clubs, Weddings & funeral services, Auctions.

Key Features

- Delivers a powerful 100 Watts of high fidelity and high efficient sound through full range
- Lightweight, compact and rugged design and accepts up to 2 receiver modules.
- Built-in retractable handle and sturdy wheels ensure easy transport.
- Built-in compartment storage for up to 2 handheld or bodypack transmitters.
 Amplification from a variety of audio sources.
- Can be mounted on a speaker stand.
- Built-in AC switching power supply/charger for universal usage and fast battery charge.
- · AC and rechargeable battery operation.

Transmitters & Microphones

ACT-30H	Handheld Transmitter
ACT-30T	Bodypack Transmitter
MM-107	Hypercardioid Dynamic Microphone

Accessories

MB-70	Sealed Lead-acid Rechargeable Battery. (12V, 4.5AH)
SC-70	Storage Cover Bag
MS-70	Tripod Speaker Stand
MA-707EXP	Passive Extension Speaker
MRM-70-R	Single-Channel Diversity Receiver Module
CDM-2P	CD/USB Player Module

Technical Specifications

Portable PA		
Max. Power Output	100 Watts	
Amplifier	Class AB	
T.H.D.	<1%	
Frequency Response	50Hz~18kHz	
Speaker	8" full-range	
	Wired: XLR× 1 & 6.3mm (1/4")× 1	
Audio Inputs	Wireless: UP to 2 wireless microphones	
Audio Inputs	CD Player: CD, USB port	
	Line-In: Unbalanced 6.3mm (1/4") jack	
Audio Output	Unbalanced line 6.3mm (1/4") jack	
Extension Speaker	6.3mm (1/4") Phone jack	
Volume	Master and other individual controls	
Controls	Tone control on wireless mics	
Storage	2 handheld or bodypack transmitters	
Installation	Speaker stand, flat surface or retractable handle & wheels	
	AC: Built-in 100-240V AC switching power supply	
Power Supply	DC & Battery: 24~32DC, 12V/4.5AH rechargeable gel cell	
	battery	
Charge Time	Up to 8 hours (automatic charging management)	
Stand-by Time	Up to 8 hours	
Battery Indicator	Single LED indicator	
Dimensions	310(W)× 445(H)× 240(D)mm / 12.2(W)x17.5(H)x9.4(D)"	
Weight	Approx. 14.8kg / 32.5lbs (battery included)	
	Wireless System (optional)	
Receiver	MRM-70	
Max. Receiver	Up to 2	
Installation	Plug-in Module	
Antenna	Built-in	
	Audio Player (optional)	
Model	CDM-2P	
Installation	Plug-in Module	







